

9460 Remote Area Lighting System

Save page as PDF



9460 Remote Area Lighting System



Using solid-state mounted LED's coupled with a thermally efficient light engine and our 1510 Protector Case, the RALS 9460 gives the user the ultimate maintenance free portable floodlight station to get the job done efficiently, safely and on time. The RALS 9460 houses both of its light heads and its multi-stage charger for that total self contained convenience, it is also equipped with a telescopic handle and rugged wheels for ease of transport.



Black



Yellow

Light Source

LED Type	LED Life	Tested Lumen Value
High Flux LED	50000	2000 (Low) 4000 (High)

Lamp Heads	Number of LEDs	Beam Spread	Brightness Settings
2	48	90	2

Power Source

Battery Type	Battery Burn Time	Battery Charging Time	Battery Life
12v Rechargeable, Sealed	14 (Low) 7 (High)	9 hrs. from full discharge	2000

Low Battery Warning	12V Primary Sockets	12V Auxiliary Sockets
Intermittent Blinking	2	

Watts	Voltage
48	12

Dimensions & Weight

Head Length	Head Width	Head Depth
16.5cm.	20cm.	6.5cm.

Width Closed	Length Closed	Height Closed
55.9cm.	35.1cm.	22.9cm.

Mast Height Extended	Cord Length	Weight
179.9 cm.	35cm.	23kg.

Materials

Head	Body	Mast
Polycarbonate/ABS	Polypropylene	Aluminium

Lens	Switch Type
Polycarbonate	Silicone rubber keypad

Configurations

Cat. #	Description
9460	9460 Remote Area Lighting System

Accessories

No accessories are currently available for this product

Approvals

RoHS (Restriction of Hazardous Substances) Compliant

