


Rugged high speed wireless 8-port Ethernet managed switch (WiFi IEEE 802.11 a / b / g / h)



Top "C-Key" for quick configuration Save & Restore

WLg-Switch

RF Module certified



IEEE 802.11a/b/g/h
WiFi 2.4 / 5 GHz

5-YEAR WARRANTY

WLg-Switch is an 8-port 10/100 managed Ethernet switch over WLAN designed for harsh industrial environments and automotive applications. The unit is housed in a compact enclosure ready to be DIN rail or panel mounted.

The device is a managed layer 2 switch that offers many switch technology advancements, including auto MDI/MDIX crossover for easy plug and play application, and administrable POE PSE; WLg-Switch can be managed using a web browser or SNMP; The "C-Key" allows for quick and easy on-site replacement of the WLg-SWITCH unit, eliminating the need to reconfigure the replacement part or to use any other equipment.

WLg-Switch fulfills the most severe requirements in terms of operating environment: operating temperature from -20°C to +70°C (-4°F to 158°F), shockproof and vibration proof according to MIL-STD-810F standard, seal rating IP40.



TECHNICAL CHARACTERISTICS

Ethernet Switch	8-port 10/100 Base TX Fast Ethernet interface, RJ45 connector, auto MDI/MDIX crossover, IEEE 802.3x full-duplex and half-duplex auto-adaptive, wire-speed reception and transmission, high performance lookup engine, automatic address learning and aging, POE PSE feature according to IEEE 802.3.af
WiFi network	Compliant to the IEEE 802.11a/b/g/h 2.4 / 5 / 5.4 GHz standards, multi-country Roaming support (IEEE 802.11d); Dynamic Frequency Selection (DFS) support provides flexible selection of best frequency to allow mobility among all existing IEEE 802.11a/b/g/h networks; "ClearVoice" band provides non-overlapping channels for fast-speed data transmission; Transmission Power Control (TPC) offers flexibility to adjust RF output power, based on the Atheros AR5414 (AR5006XS) chip set
Radio data rate	Up to 108 Mbps (Super AG mode), TCP user data rate up to 44 Mbps
Channels	13 channels (b/g modes), 8 channels (a mode), 11 channels (h mode) Number of channels may vary depending on local laws.
Output power	Transmitter +20 dBm (Optional 26 dBm)
Sensibility	Receiver -92 dBm for IEEE 802.11 a/g and -95 dBm for IEEE 802.11b
Antenna	Two 2dBi 2.4 / 5 GHz antenna for diversity mode
Modulation	OFDM: BPSK, QPSK, 16QAM, 64QAM DSSS: DBPSK, DQPSK, CCK
Security	64/128 bits WEP, WPA-PSK, WPA2-PSK, IEEE 802.11x (RADIUS supplicant & authenticator), MAC addresses filtering, SSID broadcast control
Modes	Access point to build a WiFi network infrastructure, Bridge, Bridge router, fast roaming, Infrastructure & AD-HOC modes are supported
Administration	Built-in WEB interface, SNMP V2c agent, ACKSYS NDM (Networking Device Manager). ACKSYS unique "C-Key" allows for quick and easy on-site replacement of the WLg-SWITCH unit, eliminating the need to reconfigure the replacement part or to use any other equipment
Operating systems	Windows, Linux, UNIX as well as any operating system supporting TCP/IP
Protocols	Ethernet TCP/IP & UDP, MODBUS/TCP, Ethernet/IP, PROFINET ...
Signaling	Power supplies, LAN on each port & WLAN activity on LEDs
Alarms	Relay output warning: power failure, LAN or WLAN connection failure, Watchdog. 1 FORM B solid state relay, 60V 0.15A, contacts on removable clamp cage terminal
Power supply	Dual input, +9 to +72VDC, removable clamp cage terminal for non POE PSE operation Device should be powered from a +48VDC (30 Watts) power supply in used in the POE PSE mode
Consumption	10 Watts maximum, up to 30 Watts in POE PSE mode
Dimensions & weight	L: 110mm x W: 50mm x H: 151mm (4.33"x1.97"x5.94"), weight 650g (22.9 oz)
Environment	Operating temperature: -20°C to +70°C (-4°F to 158°F), storage: -65°C to +100°C (-85°F to 212°F), Humidity: 5% to 95% (non-condensing), IP 40 seal rating

References to order

WLg-Switch	8-Port Ethernet manageable switch over WLAN including Access Point, Ethernet Bridge & Repeater modes (WiFi IEEE 802.11a/b/g/h & super AG), shipped with two 2dBi 2.4 / 5 GHz antennas
C-Key	Save / Restore configuration key for the WLg-Switch
WLg-RF400MW	High power radio option (26 dBm, 400 mW)
WLg-FIX-PLQ	Panel fixing metallic plate
CAB-RJ45-1M	1 meter Ethernet RJ45 cable, straight

All the brand names mentioned in this document are trademarks. ACKSYS is constantly looking at ways to improve its products. The current specifications may therefore be modified without notice and the characteristics set out herein should not be construed as creating any contractual obligation. All the products featured herein are designed and manufactured in Europe.