



中国·人民电器集团
PEOPLE ELE. APPLIANCE GROUP CHINA

MINI CIRCUIT BREAKER

DZ47-63 MINI CIRCUIT BREAKER

APPLICATION

DZ47-63 series circuit breaker is used in lighting distribution system or motor distribution system for protecting overload and short-circuit in the system. The product novel in structure, light in weight, reliable and excellent in performance. It has high breaking capacity, can trip quickly and its installation uses with guide, its case and items are adopted with high fire-resistant and shockproof plastic. The product, with long life, is mainly used in AC 50/60Hz single-pole 240V or two, three, four-pole 415V circuit for overload and short-circuit protection as well as for unfrequent on-and-off switching electric equipment and lighting circuit in normal case. This product conform with GB10963, IEC60898, BS3871.



DZ47-63 1P



DZ47-63 2P



DZ47-63 3P



DZ47-63 4P

SPECIFICATIONS

Rated temperature 40°C
Rated voltage 240V/415V AC
Rated current (C): 1, 3, 6, 10, 15, 16, 20, 25, 32, 40, 50, 63A (D): 6, 10, 15, 16, 20, 25, 32, 40A

Mechanical endurance lower than 20000 times				
Tropical test: 2 kinds				
Weight (g)	1P	2P	3P	4P
	102	208	308	408

DZ47-63

Standard	Rated current (A)	Pole	Voltage (V)	Breaking capacity (A)
BS3871-1 IEC60898	1 to 40	1	240	6000
		2, 3, 4	415	6000
	50 to 63	1	220/240	4000
		2, 3, 4	400/415	4000

DIMENSIONS

